


FP 10000Q (USED)

LAB.GRUPPEN

Very high power and channel density – The four-channel FP10000Q delivers a total of 10000 W (4 x 2500 W @ 2 ohms) in only 2U. Four-channel flexibility – Adjacent channels bridgeable for 2- or 3-channel operation. Lab.gruppen sound quality – impeccable sonic performance standards with durability and greater efficiency. NomadLink® network ready – Monitoring and control of key functions accessible via the intuitive DeviceControl software. Patented Class TD amplifier topology – Road-proven output stage delivers Class B audio quality with Class D efficiency. Regulated Switch Mode Power Supply (R.SMPS) – Output power remains constant even with significant drops in the mains voltage. Efficient cooling system - Unique, lightweight Intercooler copper cooling system dissipates more heat to allow extended peak output. Adjustable parameters - Selectable Gain, scalable Voltage Peak Limiter (VPL), and bridge-mode operation allow custom configuration for any application. Comprehensive protection and warning – Excessive output current, DC, high temperature, very high frequency (VHF), short circuit, open load, mains fuse protection, and soft start. XLR input connectors. Heavy-duty binding post or Speakon output connectors.

Τιμή Λιανικής

0,00€ **Στη Τιμή Λιανικής Συμπεριλαμβάνεται Φ.Π.Α. 24%

Κωδικός: E008851

Part Number:

Η Τιμή Αφορά: **Τεμάχιο**

Τελικός ενισχυτής 4 x 2500 W @ 2 ohms

Κατασκευαστής:	LAB GRUPPEN
Μοντέλο:	FP 10000Q (USED)
Part Number:	
Used Item	NAI