

## Zx3-60PI





| Manufacturer Name:       ELECTROVOICE         Model:       Zx3-60Pl         Part Number:       F01U265603         Speaker Category       Satellite (full range)         Speaker Type       Passive         Speaker Material       Plastic Cabin         Speaker Power (Watt)       600         Resistance (ohms)       8Ω         Woofer (inches)       12         Tweeter / Driver (inches)       2         dB (max spl)       131         Sensitivity (1W / 1m)       97         Weight (kg)       19.8         Frequency Response (Hz)       48 έως 20000         Color       Mαύρο         Application       Installation         Guarantee       5 Years Guarantee |                           |                        |
|---|---------------------------|------------------------|
| Part Number:       F01U265603         Speaker Category       Satellite (full range)         Speaker Type       Passive         Speaker Material       Plastic Cabin         Speaker Power (Watt)       600         Resistance (ohms)       8Ω         Woofer (inches)       12         Tweeter / Driver (inches)       2         dB (max spl)       131         Sensitivity (1W / 1m)       97         Weight (kg)       19.8         Frequency Response (Hz)       48 έως 20000         Color       Mαύρο         Application       Installation   | Manufacturer Name:        | ELECTROVOICE           |
| Speaker Category       Satellite (full range)         Speaker Type       Passive         Speaker Material       Plastic Cabin         Speaker Power (Watt)       600         Resistance (ohms)       8Ω         Woofer (inches)       12         Tweeter / Driver (inches)       2         dB (max spl)       131         Sensitivity (1W / 1m)       97         Weight (kg)       19.8         Frequency Response (Hz)       48 έως 20000         Color       Μαύρο         Application       Installation   | Model:                    | Zx3-60PI               |
| Speaker Type       Passive         Speaker Material       Plastic Cabin         Speaker Power (Watt)       600         Resistance (ohms)       8Ω         Woofer (inches)       12         Tweeter / Driver (inches)       2         dB (max spl)       131         Sensitivity (1W / 1m)       97         Weight (kg)       19.8         Frequency Response (Hz)       48 έως 20000         Color       Μαύρο         Application       Installation         Installation  | Part Number:              | F01U265603             |
| Speaker Material       Plastic Cabin         Speaker Power (Watt)       600         Resistance (ohms)       8Ω         Woofer (inches)       12         Tweeter / Driver (inches)       2         dB (max spl)       131         Sensitivity (1W / 1m)       97         Weight (kg)       19.8         Frequency Response (Hz)       48 έως 20000         Color       Μαύρο         Application       Installation         Installation   | Speaker Category          | Satellite (full range) |
| Speaker Power (Watt)       600         Resistance (ohms)       8Ω         Woofer (inches)       12         Tweeter / Driver (inches)       2         dB (max spl)       131         Sensitivity (1W / 1m)       97         Weight (kg)       19.8         Frequency Response (Hz)       48 έως 20000         Color       Μαύρο         Application       Installation         Installation  | Speaker Type              | Passive                |
| Resistance (ohms)       8Ω         Woofer (inches)       12         Tweeter / Driver (inches)       2         dB (max spl)       131         Sensitivity (1W / 1m)       97         Weight (kg)       19.8         Frequency Response (Hz)       48 έως 20000         Color       Μαύρο         Application       Installation         Installation       Installation  | Speaker Material          | Plastic Cabin          |
| Woofer (inches)       12         Tweeter / Driver (inches)       2         dB (max spl)       131         Sensitivity (1W / 1m)       97         Weight (kg)       19.8         Frequency Response (Hz)       48 έως 20000         Color       Μαύρο         Application       Installation         Installation       Installation   | Speaker Power (Watt)      | 600                    |
| Tweeter / Driver (inches)  dB (max spl)  Sensitivity (1W / 1m)  97  Weight (kg)  19.8  Frequency Response (Hz)  48 έως 20000  Color  Mαύρο  Application  Installation   | Resistance (ohms)         | 8Ω                     |
| dB (max spl)       131         Sensitivity (1W / 1m)       97         Weight (kg)       19.8         Frequency Response (Hz)       48 έως 20000         Color       Μαύρο         Application       Installation         Installation   | Woofer (inches)           | 12                     |
| Sensitivity (1W / 1m)97Weight (kg)19.8Frequency Response (Hz)48 έως 20000ColorΜαύροApplicationInstallationInstallation  | Tweeter / Driver (inches) | 2                      |
| Weight (kg)19.8Frequency Response (Hz)48 έως 20000ColorΜαύροApplicationInstallationInstallation   | dB (max spl)              | 131                    |
| Frequency Response (Hz)  Color  Mαύρο  Application  Installation  | Sensitivity (1W / 1m)     | 97                     |
| Color Μαύρο  Application Installation   | Weight (kg)               | 19.8                   |
| Application Installation Installation   | Frequency Response (Hz)   | 48 έως 20000           |
| Installation  | Color                     | Μαύρο                  |
|   | Application               | Installation           |
| Guarantee 5 Years Guarantee   |                           | Installation           |
| 0 / 54.75   | Guarantee                 | 5 Years Guarantee      |

Retail Price **1.942,00€** \*

\*VAT Included in Retail Price 24%

Code: 001975-( $\Delta$ )

Part Number: F01U265603

Price for: pcs

Passive loudspeaker 2 way 12", 600W RMS

/8 ohm