



Benchmark power density – The FP 7000 delivers a total of 7000 W (2 x 3500 W @ 2 ohms) in only 2U. Lab.gruppen sound quality – impeccable sonic performance standards with durability and greater efficiency. NomadLink® network ready – Monitoring and control of key functions accessible via the intuitive DeviceControl software. Patented Class TD amplifier topology – Road-proven output stage delivers Class B audio quality with Class D efficiency. Regulated Switch Mode Power Supply (R.SMPS) – Output power remains constant even with significant drops in the mains voltage. Efficient cooling system - Unique, lightweight Intercooler copper cooling system dissipates more heat to allow extended peak output. Adjustable parameters - Selectable Gain, scalable Voltage Peak Limiter (VPL), and bridge-mode operation allow custom configuration for any application. Comprehensive protection and warning – Excessive output current, DC, high temperature, very high frequency (VHF), short circuit, open load, mains fuse protection, and soft start. XLR input connectors. Heavy-duty binding post or Speakon output connectors

Retail Price
4.350,00€ *

*VAT Included in Retail Price 24%

Code: E008176-(A)

Part Number: 992166051

Price for: pcs

2-channel power amplifier 2 x 2800W 4Ω

Manufacturer Name:	LAB GRUPPEN
Model:	FP 7000 /SP
Part Number:	992166051
Channels	Dual Channel
Resistance ohms	4Ω / 16Ω, 2Ω
Power (8 ohms/Watt RMS) per channel	1450
Power (4 ohms/Watt RMS) per channel	2800
Power (2 ohms/Watt RMS) per channel	3500
Application	Concert, Installation, Portable PA
Weight (kg)	12
	Installation,Rental
Guarantee	10 Years Guarantee