

MAUI 44G2



The LD Systems MAUI® 44 G2 is the flagship of the MAUI series column PAs: it 1,500 watts of total output (RMS) with a frequency response of 37 Hz to 20 kHz and a sound-level pressure of 132 dB (peak). The cardioid properties of the column elements and the possibility of creating a cardioid bass with an additional subwoofer further highlights the professional nature of this sound system. The column achieves a rear attenuation of 18 dB, the subwoofer 15 dB. The MAUI® 44 G2 also sets the tone when the two-part column is equipped with twelve 3.5" neodymium full-range speakers and four 1" HF drivers with waveguide. The phase plugs on the six upper drivers improve horizontal directivity, reduce distortion and optimise the sensitivity below the crossover frequency for the tweeters. In addition, the four tweeters feature specially designed and optimised compression drivers coupled to a constant directivity waveguide to provide 120° of coverage across the width and 25° of focused vertical directivity. The curved design of the waveguide transports more energy in the high frequencies to listeners standing further away.

| | |
|--------------------|------------|
| Manufacturer Name: | LD SYSTEMS |
| Model: | MAUI 44G2 |
| Part Number: | LDMAUI44G2 |

Retail Price
3.763,00€ *

*VAT Included in Retail Price 24%

Code: E018725-(A)
Part Number: LDMAUI44G2

Price for: pcs

Cardioid powered Column Loudspeaker